

6 In. 15W (32W Replacement) Selectable White G13 Base (T8 Or T8 And T12 Replacement) U-Bend Linear LED Tube

Features

- Two installation options: plug and play direct replacement or ballast bypass
- Shatter-resistant and mercury-free, no special disposal is required
- Flicker-free, instant ON illumination at full brightness
- **Ideal usage:** General purpose lighting, Task Lighting



Specifications

| | | | |
|--------------------------------|----------------------------|-------------------------------|------------------------------|
| Item Number | Item Length (In) | Item Width (In) | Bulb Shape |
| T848/3CCT/U6/LED | 22.7 | 6.9 | T8 |
| Bulb Type | Bulb Base | Bulb Finish | Tube Type |
| Tubular | G13 | White | Type A/B |
| Technology | Brightness (LUMENS) | Lumen Efficiency (LPW) | Color Accuracy (CRI) |
| LED - SMD | 2100 | 140.0 | 80 |
| Color Temperature (CCT) | Life Hours | Life Years | Voltage |
| 3000 4000 6500 | 50000 | 45.7 | 120-277 |
| Replacement | Annual Energy Cost | Energy Efficiency | Energy Used (Wattage) |
| 32 | 1.81 | 53.1% | 15 |
| Battery Operated | Pack Quantity | Smart | Portable |
| No | 1 | No | No |
| Dimmable | Hardwire | Enclosed Fixture Rated | Safety Location |
| No | No | No | Damp |
| CEC Compliant | | | |
| Not Regulated | | | |