

# 6 In. 15W (32W Replacement) Daylight (5000K) G13 Base (T8 And T12 Replacement) Direct Replacement And Ballast Bypass (Type AB) U-Bend Linear LED Tube

## Features

- Two installation options: plug-and-play direct replacement or easy ballast bypass
- Shatter-resistant and mercury-free, no special disposal is required
- Flicker-free, instant ON illumination at full brightness
- **Ideal usage:** Office, Garage or Warehouse Lighting



## Specifications

Item Number	Item Length (In)	Item Width (In)	Item Height (In)
T848/850/AB/U6/LED	22.6	7.0	1.2
Bulb Shape	Bulb Type	Bulb Base	Tube Type
T8	Tubular	G13	Type A/B
Brightness (LUMENS)	Lumen Efficiency (LPW)	Color Accuracy (CRI)	Color Temperature (CCT)
2100	140.0	80	5000
Life Hours	Life Years	Voltage	Replacement
50000	45.7	120-277	32
Annual Energy Cost	Energy Used (Wattage)	Battery Operated	Pack Quantity
1.81	15	NO	1
Smart	Portable	Dimmable	Hardwire
No	NO	NO	NO
Enclosed Fixture Rated	Safety Location	Energy Star	CEC Compliant
YES	Damp	No	Not Regulated